



DAZZLE BURNISHING CREAM

For Resilient Tile, Marble & Stone Floors

Enhance Burnishing creme is designed for use on all floors which can be buffed or burnished with high speed machines. DAZZLE BURNISHING CREAM penetrates, cleans, restores and rejuvenates floors in one operation creating a tough, durable "Thermal Shield of Shine."

Excellent for use on resilient, stone, terrazzo, marble, granite slate or other natural floors.

Best results are obtained when at least three coats of our buffable seals and finish products are used as a base.

Works well on hard-to-coat natural stone floors with or without a seal coat.

Application: Apply a short stream of DAZZLE BURNISHING CREAM in front of machine. Spread, buff and burnish floor using burnish pad. A short stream will clean, polish and restore approximately 600-1200 square feet. An optional method is to apply small drops on floor and then buff and burnish.

DIRECTIONS:

PAD TYPE: red, white, beige, yellow hair

MACHINE TYPE: Electric, battery or propane. Works at any speed. Best results are obtained at speeds above 1,000 rpm.

1. Dust mop the floor, and while doing so remove all gummed labels and chewing gum.
2. Apply a 3" long stream of ENHANCE BURNISHING CREAM Burnishing Creme in front of machine and spread over an area approximately 600-1200 sq. ft. This will clean and polish in one operation.
3. Dust mop again to remove all the dried soil deposits.

RECOMMENDED USES:


- Resilient Floors
- With Any Buffing Pad or Machine
- Natural or Stone Floors
- As a Base on Hard-to-Coat Floors

BENEFITS:

- Cleans, Shines, Protects
- Brilliant, Durable, Deep Shine
- Resists Scratches, Scuffs and Marking
- Slip Resistant
- Versatile
- Economical
- Can Be Recoated

TECHNICAL DATA:

Appearance.....Opaque, Thick Creme
 OdorCitrus
 Viscosity2,000 cps
 Slip Resistance.....Exceeds .5 coefficient of friction as measured on the James Machine after buffing
 FilmClear, flexible film
 Removability.....Selective Stripper (Emulsifier)
 Black Mark ResistanceExcellent
 Slip Resistance.....Excellent
 Biodegradability.....Complete



SOLD EXCLUSIVELY BY:



Wausau, WI 54402
(800) 826-4405


To Reorder: 1-888-722-5508
or visit www.cleanfreak.com

1091/10-25-2006



HAZARD RATING

4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT



MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910.1200)

Date Prepared: 10-24-06

SECTION 1 - PRODUCT IDENTIFICATION

Company Name	PTI - Packaging Tape Inc	Emergency Telephone No.	1-800-535-5053
Address	4900 W. Stewart Avenue, Wausau, WI 54402	Information Telephone No.	1-800-826-4405
Product Name / ID#	Dazzle (1091)	Product Type	Burnishing Creme <input checked="" type="checkbox"/> Proprietary Product

SECTION 2 - HAZARDOUS INGREDIENTS

Chemical Name/Common Name	Cas No.	Percent (optional)	TLV (Source)
None			

* Substances Contains no substances - subject to the reporting requirements of SARA 313 and 40 CFR Part 372.

SECTION 3 - PHYSICAL DATA

Boiling Point (°F)	212°F	Specific Gravity (H ₂ O=1.0)	1.008 ± 0.005	pH	9.5 ± 0.5	% VOC (ww)	0.50%
Solubility In Water	Unknown	<input checked="" type="checkbox"/> Complete	<input type="checkbox"/> Insoluble	<input type="checkbox"/> Emulsifiable or (Dispersible)	<input type="checkbox"/> Slight (or Partial)		
Evaporation Rate (vs H ₂ O)	<input type="checkbox"/> Faster	<input checked="" type="checkbox"/> Slower	<input type="checkbox"/> About the Same	Vapor Pressure	Unknown	Vapor Density	Unknown

Appearance and Odor Clear, viscous liquid, citrus odor.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (T.C.C.)	<input checked="" type="checkbox"/> None to boiling	Flammable Limits	Upper	NA	Lower	NA
Extinguishing Media	NA					
Special Fire Fighting Procedures	NA					
Unusual Fire Explosion Hazards	NA					

SECTION 5 - REACTIVE DATA

Stability	Stable	Incompatibility	None
Hazardous Decomposition Products	None		

SECTION 6 - HEALTH HAZARDS

Threshold Limit Value Product See Section 2 for Ingredients TLV	<input checked="" type="checkbox"/> None Established	<input type="checkbox"/> Not Applicable	Primary routes of Exposure	<input checked="" type="checkbox"/> Eyes	<input checked="" type="checkbox"/> Skin	<input checked="" type="checkbox"/> Oral	<input type="checkbox"/> Inhalation
--	--	---	----------------------------	--	--	--	-------------------------------------

Signs Symptoms of Over-exposure (Acute) Burning sensation and irritation to the eyes. Prolonged skin contact may cause irritation.
May cause gastro intestinal irritation if swallowed.

Signs Symptoms of Over-exposure (Chronic) Unknown

Medical Conditions Aggravated by Over-exposure Unknown

Carcinogen/Suspected Carcinogen Ingredients: NTP IARC OSHA None

SECTION 7 - FIRST AID PROCEDURES - (If any Condition persists - Consult a physician.)

Eyes Flush with water for 10-15 minutes. If irritation persists, see a physician.

Skin Wash with water for 5-10 minutes. Remove any contaminated clothing and wash before reuse.

Ingestion Give large quantities of water to dilute contents. Get medical attention if irritation persists.

Inhalation NA

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection None

Ventilation requirements Local Exhaust Mechanical Normal ventilation should be adequate.

Protective Gloves Rubber gloves if prolonged contact. Eye Protection Safety goggles

Other Protective Clothing None

SECTION 9 - SPILL OR LEAK PROCEDURES

Steps to be Taken if Released or Spilled Mop up, rinse with water.

Waste Disposal Methods Flush into sanitary sewer system. Check all government regulations.

SECTION 10 - STORAGE AND HANDLING INFORMATION

Precautions to be Taken in handling and Storage Store so as to inaccessible to children.