



EnviroStar All Purpose Neutralizer is a concentrated “green” neutralizing solution that is effective on resilient tile and all types of stone flooring. It increases adhesion of coatings to floors where alkalinity is a problem.

DIRECTIONS

Read all directions and Safety Data Sheets (SDS) before using.

NEUTRALIZING FLOOR AFTER STRIPPING

1. Dilute product at 1:10 (13 US oz per gallon of water or 500 ml per 5 liters of water).
2. Apply with mop or automatic scrubber to neutralize hard floors.
3. Allow to soak for 10 minutes, rinse with water and allow to dry thoroughly before applying sealer and/or coating. To neutralize vinyl floors, dilute at 1:64 (2 US oz per gallon of water or 80 ml per 5 liters of water).

REMOVING SALT FILMS

1. Clean floors to remove soil residues.
2. Mix product per the following dilutions: Removal of light to moderate winter salt films: 1:128 (1 US oz per gallon or 40 ml per 5 liters of water) in mop bucket or automatic scrubber.
Removal of heavy winter salt films: 1:64 (2 US oz per gallon of water or 80 ml per 5 liters of water).
3. Pick up solution and allow floor to dry thoroughly before burnishing.

SURFACES



VCT

HARD FLOOR
SURFACES

TECHNICAL DATA

Description	All purpose neutralizer
Appearance	Clear, colorless liquid
pH	2.2 (as supplied)
	ASTM E70-07
Viscosity (Brookfield)	<10 centipoise
	@ 68°F (20°C)
Fragrance	None added
Shelf Life	2 years
	ASTM D1791-93 (2008)
Density	8.7 lb/gal @ 68°F
	ASTM D1475-98 (2008)
VOC	0.08% (as supplied)
	40 CFR Part 59 Subpart C
	<0.01 (1:10)
	<0.01 (1:64)
Container	1.06 US gal/4 L (MPE packaging)

PRODUCT INFO

Product Code	338MPE
Volume	4 liters
Shipping Package	4 x 4 liters
Pallet Quantity	48



CARB
Compliant

