Material Safety Data Sheet	-	J.S. DEPARTMENT OF LABOR				
May be used to comply with OSHA=S Hazard Communication Standard	Occupational Safety and Health (Non-Mandatory Form)					
29 CFR 2910.1200. Standard must be		m Approved				
consulted for specific requirements.	0	MB No. 1218-0072				
Identity (As Used on Label and List) Big D Para Block #900, 903, 950, 930, 960, 970, 980, 990		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.				
Section I						
Manufacturer=s Name Big D Industries, Inc.		Emergency Telephone Number (800) 535-5053 (800) 654-4752				
Address (number, Street, City, State, and ZIP Code) 5620 S. W. 29th Street (73179)		Telephone Number for Information   (800) 654-4752 (405) 682-2541				
P. O. Box 82219		Date Prepared 01/01/2007				
Oklahoma City, OK 73148		Signature of Preparer (optional)	Signature of Preparer (optional)			
Section II - HMIS Rating						
Health 2 Flammability 2		Reactivity 0				
Section III - Hazardous Ingredients/Identity	<b>Information</b>					
Hazardous Components [Specific Chemical Identity: Common Name(s)] OSHA PEL ACGIH TLV Other Limits % (optional) Recommended						
Para Dichlorobenzene*75 ppm10 ppm 110 ppm99.65[(1,4.Dichlorobenzene), PDCB] CAS #106-46-78HR TWA(ACGIH-STEL)						
DOT Hazard Class / ID No / Packaging Group	9/UN3077/III					
*This product contains Para Dichlorobenzene which is def Amendments and Reauthorization Act of 1986 and 40 CF		ical and subject to the reporting requirements of '313 of Title III of ta Prop 65 listed chemical.	the Superfund			
Section IV - Physical/Chemical Char	racteristics					
Boiling Point	345.2 °F/174°C	Specific Gravity (H <sub>2</sub> O = 1) @ 55 ${}^{0}F / 4 {}^{0}C$ 1.	.245 - 1.250			
Vapor Pressure (mm Hg.) @ $25 {}^{0}$ C	0.92	Melting Point 12	27.4 °F/53 °C			
Vapor Density (AIR = 1)	5.1	Evaporation Rate	N/A			
Solubility in Water: @ $25$ $^{\circ}$ C, % by Wt. 0.008						
Appearance and Odor: White block with penetrating Amothball@ odor.						
Section V - Fire and Explosion Haza	rd Data					
Flash Point (Method Used) Flash 150 °F (TCC)			LEL UEL 2.5 N/E			
Extinguishing Media Water spray, foam, CO <sub>2</sub> ,	dry chemical, or a	any Class B extinguishing agent				
Special Fire Fighting Procedures Wear full protective clothing and NIOSH/MSHA approved self contained breathing apparatus where exposure to vapors is possible.						
Unusual Fire and Explosion Hazards Highly toxic g of this product.	ases (Hydrogen C	Chloride, Chlorine, and traces of Phosgene) can be evo	lved in fires			
N/A = Not Applicable N/D = Not Determine	ed $N/E = Not$	t Established Page 1 OSHA	174, Sept. 1985			

#9	00-	.99	0
$\pi 2$	00-	・フフ	υ

Section VI -	Reactivity Data					
Stability	Unstable		Conditions to Avoid: Keep away from open flame and sparks.			
	Stable	Х				
Incompatibility (Ma	aterials to Avoid): Stron	g oxidize	rs, oxidizing agents, hot aluminum	or aluminum alloys		
Hazardous Decomp	position or Byproducts: C	arbon Mo	onoxide, Carbon Dioxide, smoke, s	oot, Hydrogen Chloride and Phosgene		
Hazardous Polymerization	May Occur		Conditions to Avoid: None			
	Will Not Occur	X				
Section VII	- Health Hazard D	ata				
Route(s) of Entry:	Inhalation? Yes	Skir	n? Yes Ingestion?	Yes (Unlikely)		
				well above per can cause depression of the o cause liver damage in rats and rabbits.		
		substance		A Regulated? be@ carcinogenic. IARC has been classified as op. 65.		
Signs and Sympton sensitization if	ns of Exposure: Headac concentration above TL		ness; eyes, nose and throat irritation	; nausea; feeling of drunkenness; cardiac		
Medical Conditions	s Generally Aggravated by Ez	xposure:	Asthma or other respiratory disor	ders; blood, liver and kidney disorders		
affected area w	ith plenty of water for a	t least 15	minutes; if irritation develops, get	nutes; get medical attention. Skin - flush medical attention. Inhalation - remove person to Ingestion - do not induce vomiting; get medical		
Section VIII	- Precautions for	Safe Ha	andling and Use			
Steps to be Taken in Case Material is Released or Spilled: Scoop up and put in closed container.						
-	ethod: Material should b federal regulations.	e burned	in an approved incinerator or dispo	sed of in an approved dump in accordance with		
Other precautions:	Store away from he	at and op	en flame. Avoid excessive inhalati	on and contact with skin and eyes.		
Section IX -	<b>Control Measures</b>	;				
Respiratory Protect	ion (Specify Type):					
Ventilation			Local Exhaust Well Ventilated	Special N/A		
			Mechanical (General) N/A	Other N/A		
Protective Gloves:	None		Eye Protection: Do not rub eye	Eye Protection: Do not rub eyes with contaminated hands		
Other Protective Cl	othing or Equipment: Eye	wash/sho	ower facility nearby			
Work/Hygienic Pra in contact with		eping pra	ctices. Avoid skin/eye contact. Wa	sh thoroughly with soap and water after coming		