



REINVENT HOW THE WORLD CLEANS



T600

Industrial-strength floor scrubber

Delivering exceptional cleaning performance and reliability even in the toughest environments.

Available technologies



ec-H₂O NanoClean® technology



Pro-Membrane™
or Pro-Panel™



IRIS® Asset Manager




Smart-Fill™ Automatic
Battery Watering



High capacity battery
power sources

Productive & versatile



1. Yellow debris tray

Helps prevent machine clogging.

2. Productivity-boosting

Maximize battery life and run-time with the optional Smart-Fill™ automatic battery watering system.

3. Integrated p-trap

Virtually eliminate water compartment drain tube drips after cleaning.

4. Quiet-Mode™

Reduce noise levels as low as 62 dBA for daytime cleaning without disruption. Perfect for healthcare, education, and office cleaning.

5. On-demand training

Optional LCD Pro-Panel® resources include maintenance videos and information in 28 languages.

6. Diamabrush™ technology

Help floors battered by grime and filth look like-new with optional Diamabrush tools.

Get the performance you need

The T600 scrubbers have multiple machine head types to fit your cleaning applications and optimize cleaning performance for specific areas.



Cylindrical:

28 in / 700 mm &
32 in / 800 mm



Dual disk:

28 in / 700 mm &
32 in / 800 mm &
36 in / 900 mm

Inside the T600



1. Simplify operation

Easy-to-understand controls featuring variable speed control bail, propel toggle and speed setting within easy reach.

2. Recovery hose

Pinch-style recovery hose helps control dirty water flow.

3. Convenient charger

Charge anywhere with the convenient on-board charger.

4. Foot activated squeegee

Easily and ergonomically lower and raise the foot activated squeegee.

5. Yellow touch points

Save time and ensure proper maintenance with yellow touch points.

6. Drain tube

Safely control the removal of excess fluids via the battery compartment drain tube.

7. Easy access

To solution filter bowl makes cleanout simple and quick.

8. Foam filled or pneumatic tires

Increase traction with tires with enhanced grip.

9. Yellow plunger

Easily remove scrub head brushes with yellow plunger.

T600 specifications

	DUAL DISK			CYLINDRICAL	
	28 IN/700 MM	32 IN/800 MM	36 IN/900 MM	28 IN/700 MM	32 IN/800 MM
Productivity (per hour) Theoretical Max	36,960 ft ² /hr	42,240 ft ² /hr	47,520 ft ² /hr	36,960 ft ² /hr	42,240 ft ² /hr
	3,434 m ² /hr	3,924 m ² /hr	4,415 m ² /hr	3,434 m ² /hr	3,924 m ² /hr
Estimated Coverage* Conventional	24,005 ft ² /hr	27,698 ft ² /hr	31,391 ft ² /hr	24,005 ft ² /hr	27,698 ft ² /hr
	2,230 m ² /hr	2,573 m ² /hr	2,916 m ² /hr	2,230 m ² /hr	2,573 m ² /hr
Estimated Coverage* ec-H2O NanoClean®	28,863 ft ² /hr	33,304 ft ² /hr	34,964 ft ² /hr	28,863 ft ² /hr	33,304 ft ² /hr
	2,681 m ² /hr	3,094 m ² /hr	3,248 m ² /hr	2,681 m ² /hr	3,094 m ² /hr
Scrub motor	2 x 36 VDC, 1.0 hp/.75 kW			2 x 36 VDC, .9 hp/.67 kW	
Brush/pad RPM	300 rpm			760 rpm	
Brush/pad pressure	100, 150, 200 lbs/ 45, 68, 90 kg	100, 150, 200, 300 lbs / 45, 68, 90, 136 kg	100, 150, 200 lbs/ 45, 68, 90 kg	50, 70, 90 lbs/23, 32, 41 kg	
Solution tank capacity	32 gal / 121 L			32 gal / 121 L	
Recovery tank capacity	37 gal / 140 L			37 gal / 140 L	
Vacuum motor	36 VDC, 0.75 hp/.56 kW, 15.6 A			36 VDC, 0.75 hp/.56 kW, 15.6 A	
Vacuum waterlift	50 in / 1,270 mm			50 in / 1,270 mm	
System voltage	36 volt			36 volt	
Battery run time (up to hours)**	5.4	5.3	5.3	6.9	6.1
Battery option packages	Wet 240 AH Wet 360 AH 210 AH Thin Plate Pure Lead (TPPL) *****				
Length x width x height	63.7 x 30.1 x 43.6 in 1,617 x 764 x 1,107 mm	65.8 x 33.7 x 43.6 in 1,617 x 856 x 1,107 mm	69.3 x 37.6 x 43.6 in 1,761 x 955 x 1,107 mm	64.4 x 31.2 x 43.6 in 1,637 x 792 x 1,107 mm	64.4 x 35.1 x 43.6 in 1,637 x 892 x 1,107 mm
Weight (with Batteries)	1,033 lb/470 kg	1,036 lb/471 kg	1,040 lb/473 kg	1,049 lb/477 kg	1,052 lb/478 kg
Sound level (operator's ear)***	69.5 dBA			69.2 dBA	
Quiet-Mode (operator's ear)***	62.2 dBA			62.2 dBA	
T600***** - approvals (U.S./Canada only) - ETL Listed to UL 583 Type E					



ec-H2O NanoClean® technology is NFSI
(National Floor Safety Institute) Certified



ec-H2O NanoClean technology is registered
by NSF International

*Estimated coverage rates use the practical speed and empty/fill time standards from the 2014 ISSA 612 Cleaning Times & Tasks handbook.

**Up to run-times are based on continuous scrubbing run-times, 360AH batteries, low down pressure, ec-H2O off.

***Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment manufacturers & OSHA.

*****Does not include - ec-H2O NanoClean or Smart-Fill options.

*****Available in US and Canada only

Tennant – Reinvent how the world cleans

With a vision to become a global leader in sustainable cleaning innovation that empowers our customers to create a cleaner, safer and healthier world, Tennant creates solutions that are changing the way the world cleans.



We are where you are

Tennant has the industry's largest direct sales and service organization and a well-supported network of authorized distributors worldwide.



Solutions for your unique needs

Whatever your cleaning needs, Tennant offers a variety of high quality equipment to help you increase your cleaning productivity.



Buying, leasing, renting

We offer flexible options to get you the machines you need, however you need them.



TennantTrue®

Optimize equipment performance and protect your investment with TennantTrue® parts and service.

For a demonstration or additional information,
call **+1.800.553.8033** or email **info@tennantco.com**

Tennant Company

10400 Clean Street
Eden Prairie, MN 55344-2650, USA

USA/Canada: +1.800.553.8033

Quebec: +1.800.361.9050

Overseas: +1.763.540.1315

www.tennantco.com | info@tennantco.com