



CT15

4/5 GALLON, 14" BRUSH DRIVE

THE CT15, WITH GREAT TANK CAPACITY, GUARANTEES A PRODUCTIVITY OF UP TO 13,500 FT²/H. ITS COMPACT SIZE ALLOWS THE OPERATOR TO FIT INTO THOSE TIGHT AREAS, MAKING IT IDEAL FOR SMALL SPACES.

MAIN FEATURES

GREAT MANEUVERABILITY
YELLOW TOUCHPOINTS
ERGONOMIC AND EASY TO MAINTAIN

FIELDS OF APPLICATION

HEALTHCARE
RETAIL
OFFICES



HERO INNOVATIONS



ECO
SELECT



TRANSPORT
WHEEL



CARPET
KIT

.01

ADJUSTABLE HANDLE

Different position adjustment.



..... .02

REMOVABLE TANKS

High density polyethylen tanks. Metal chassis with anti-corrosion treatment.

.03

MOTORS

Brush motor with oil bath reduction gear box. Three-stage suction motor.



..... .04

BATTERIES AND CHARGERS

24 V batteries and DBL charger intergated in the machine.

		CT15 B35 BATTERY DISC	CT15 C 35R ELECTRIC CYLINDRICAL	CT15 B35 R BATTERY CYLINDRICAL	CT15 C35 ELECTRIC DISC
Max theoretical productivity	ft ² / h - m ² /h	13,500 ft ² / 1300 m ²	13,500 ft ² / 1300 m ²	13,500 ft ² / 1300 m ²	13,500 ft ² / 1300 m ²
Cleaning path	in/ mm	14" / 350 mm	14" / 350 mm	14" / 350 mm	14" / 350 mm
Water tank capacity (solution recovery)	Gal/ l	4/5 Gal 16/19 l	4/5 Gal 16/19 l	4/5 Gal 16/19 l	4/5 Gal 16/19 l
Max running time	min	90	Unlimited	90	Unlimited
Voltage		24(2x12)-29 AGM	110-50/60	110-50/60	24 (2X12) 29 agm
Installed power	W	550	400	550	400
Brush pressure	lbs/ kg	55 lbs/ 25 kg	35 lbs/ 16 kg	55 lbs/ 25 kg	35 lbs/ 16 kg
Squeegee width	in/mm	18 in/ 450 mm	18" /450 mm	18" / 450 mm	18" / 450 mm
Max speed	mph/ kph	2.2 mph/ 3.5 kph	2.2 mph/ 3.5	2.2 mph/ 3.5	2.2 mph/ 3.5
Weight	lbs/ kg	130 lbs/ 59 kg	115 lbs/ 52 kg	130 lbs/ 59 kg	115 lbs/ 52 kg
Dimension (LxWxH)	in / mm	37 x 22 x 48 in	37 x 22 x 48 in	37 x 22 x 48 in	37x21x48 in



IPC Eagle
3650 Dodd Road Eagan, MN 55123
800.486.2775
www.ipceagle.com