

# MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

**Product number** 13914  
**Product name** **Metal Polish-Lemon**  
**Effective date** 26-Dec-2012  
**Company information** Terand Industries  
PO Box 667770  
Pompano Beach, FL 33069 United States  
**Company phone** General Assistance 954-974-5440  
**Emergency telephone US** 1-866-836-8855  
**Emergency telephone outside US** 1-952-852-4646  
**Version #** 06  
**Supersedes date** 29-Nov-2011

## 2. Hazards Identification

**Emergency overview** Aerosol. EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE.  
Harmful in contact with eyes. Prolonged exposure may cause chronic effects.

**Potential health effects**

**Routes of exposure** Eye contact. Inhalation. Skin contact. Ingestion.

**Eyes** Contact with eyes may cause irritation.

**Skin** Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

**Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal.  
Prolonged inhalation may be harmful.

**Ingestion** Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.  
Components of the product may be absorbed into the body by ingestion.

**Target organs** Central nervous system. Lungs.

**Chronic effects** Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage.  
Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

**Signs and symptoms** Discomfort in the chest. Narcosis. Coughing. Conjunctivitis. Defatting of the skin. Skin irritation.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	30 - 40
Propane	74-98-6	10 - 15
Acetone	67-64-1	10 - 15
Methyl Acetate	79-20-9	8 - 10
Non-hazardous and other components below reportable levels		20 - 40

## 4. First Aid Measures

**First aid procedures**

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Skin contact** Wash off with warm water and soap. Get medical attention if irritation develops and persists.

**Inhalation** If symptoms develop move victim to fresh air. Call a physician if symptoms develop or persist.

**Ingestion**

If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not induce vomiting without advice from poison control center. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

### 5. Fire Fighting Measures

<b>Flammable properties</b>	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
<b>Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Water fog. Alcohol foam. Dry chemical. Carbon dioxide (CO2).
<b>Protection of firefighters</b>	
<b>Protective equipment and precautions for firefighters</b>	In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

### 6. Accidental Release Measures

<b>Methods for containment</b>	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.
<b>Methods for cleaning up</b>	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

### 7. Handling and Storage

<b>Handling</b>	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid contact with skin. Avoid prolonged exposure.
<b>Storage</b>	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

### 8. Exposure Controls / Personal Protection

**Exposure limits****ACGIH**

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
Methyl Acetate	79-20-9	200 ppm	250 ppm	Not established

**OSHA**

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Methyl Acetate	79-20-9	200 ppm	Not established	Not established

**Personal protective equipment**

<b>Eye / face protection</b>	Chemical goggles are recommended.
<b>Skin protection</b>	No special protective equipment required.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

### 9. Physical & Chemical Properties

<b>Appearance</b>	Compressed liquefied gas.
-------------------	---------------------------

<b>Boiling point</b>	392 °F (200 °C) estimated
<b>Color</b>	Colorless.
<b>Density</b>	0.7465 g/cm <sup>3</sup> estimated
<b>Flammability (HOC)</b>	33.5261 kJ/g estimated
<b>Flash back</b>	Yes
<b>Flash point</b>	-156 °F (-104.4 °C) Propellant
<b>Form</b>	Aerosol.
<b>Freezing point</b>	Not available
<b>Odor</b>	fruity
<b>pH</b>	Not Applicable
<b>Physical state</b>	Liquid.
<b>Pressure</b>	45 - 65 psig @ 70F
<b>Solubility</b>	Negligible
<b>Specific gravity</b>	0.7466 estimated

## 10. Chemical Stability & Reactivity Information

<b>Chemical stability</b>	Risk of ignition.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological Information

<b>Acute effects</b>	Acute LC50: 14 mg/l/4h estimated, Rat, Inhalation	
<b>Component analysis - LD50</b>		
<b>Toxicology Data - Selected LD50s and LC50s</b>		
Acetone	67-64-1	Oral LD50 Rat 5800 mg/kg
Methyl Acetate	79-20-9	Inhalation LC50 Rat 16000 ppm 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >5000 mg/kg
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
<b>Sensitization</b>	Not expected to be hazardous by OSHA criteria.	
<b>Teratogenicity</b>	Not expected to be hazardous by OSHA criteria.	

## 12. Ecological Information

<b>Ecotoxicity</b>	LC50 118 mg/L, Fish, 96.00 Hours, EC50 2784 mg/L, Daphnia, 48.00 Hours, IC50 1123 mg/L, Algae, 72.00 Hours, Contains a substance which causes risk of hazardous effects to the environment.
--------------------	--

## 13. Disposal Considerations

<b>Waste codes</b>	D001: Waste Flammable material with a flash point <140 F
<b>Disposal instructions</b>	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001.

## 14. Transport Information

### Department of Transportation (DOT) Requirements

#### Basic shipping requirements:

Proper shipping name	Aerosols
Hazard class	2.1
UN number	UN1950
Additional information:	
Special provisions	153, N82
Packaging exceptions	LTD QTY
Packaging non bulk	None
Packaging bulk	None



#### Further information

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking but not concurrently.

### IMDG

#### Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



### IATA

#### Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



## 15. Regulatory Information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

### CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	Yes
Hazard categories (311/312)	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**State regulations****U.S. - Pennsylvania - RTK (Right to Know) List**

Acetone	67-64-1	Environmental hazard
Methyl Acetate	79-20-9	Present
Propane	74-98-6	Present
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Present

**16. Other Information****Further information**

HMIS® is a registered trade and service mark of the NPCA.

**HMIS® ratings**

Health: 1\*  
 Flammability: 4  
 Physical hazard: 0  
 Personal protection:

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

**MSDS sections updated**

This document has undergone significant changes and should be reviewed in its entirety.

**Prepared by**

Regulatory Compliance